

# FLATRON L1510S FLATRON L1510S

15" (15.0" VIS) ACTIVE MATRIX LCD COLOR MONITOR



- ▶ **Brilliant Active Matrix TFT Display**
- ▶ **Auto-Synchronous Support from 640 x 350 up to 1024 x 768 @ 75Hz**
- ▶ **Simple One Touch-Auto-Setup Function**
- ▶ **LightView Function (Brightness Control)**
- ▶ **VESA DDC2B, DDC1, Plug and Play Compatible**
- ▶ **Universal 90-264 VAC Power**
- ▶ **EPA Energy Star and VESA DPMS Compliant**
- ▶ **TCO'99 Low-Emission Compliant**

**FLATRON™**



FLATRON L1510S

FLATRON L1510S

15" (15.0" VIS) ACTIVE MATRIX LCD COLOR MONITOR

FLATRON L1510S [www.LGusa.com](http://www.LGusa.com)

The LG Flatron L1510S is the perfect space saving monitor with the quality and reliability you expect from LG. With auto-synchronous support from 640 x 350 up to 1024 x 768 @ 75Hz and a brilliant active matrix TFT display, viewing is a joy. Plus it is PC and MAC compatible, has great features like simple one button auto setup and is VESA DDC2B, DDC1, Plug and Play compatible - all in a slim design. The FLATRON L1510S Active Matrix LCD Color Monitor from LG. Delightfully Smart.

<b>DISPLAY TYPE</b>	15.0" (15.0" VIS) Active Matrix TFT Color LCD Screen
<b>DISPLAY AREA</b>	12.0" x 9.0" (304mm x 228mm)
<b>DISPLAY COLORS</b>	More than 16.1 Million (6 Bit + FRC)
<b>PIXEL PITCH</b>	0.297mm x 0.297mm Pixel
<b>PIXEL CONFIGURATION</b>	RGB Stripe Arrangement
<b>SURFACE TREATMENT</b>	Hard Coating 3H, Anti-Glare
<b>ELECTRONIC INTERFACE</b>	LVDS
<b>BACKLIGHTING</b>	2CCFL
<b>MAXIMUM RESOLUTION</b>	1024 x 768
<b>BRIGHTNESS</b>	250cd/m <sup>2</sup> (Typical)
<b>CONTRAST RATIO</b>	400:1 (Typical)
<b>RESPONSE TIME</b>	16ms (Typical)
<b>VIEWING ANGLE</b>	H: 160°, V: 140°
<b>HORIZONTAL SCANNING FREQUENCIES</b>	31-63kHz, Auto-Synchronous
<b>VERTICAL SCANNING FREQUENCIES</b>	56-75Hz, Auto-Synchronous
<b>AUTO-SYNC SUPPORT</b>	640 x 350 up to 70Hz, 640 x 480 up to 75Hz, 720 x 400 up to 70Hz, 800 x 600 up to 75Hz, 832 x 624 up to 75Hz, 1024 x 768 up to 75Hz
<b>CONTROL TYPE</b>	On-Screen Display of Adjustments
<b>INPUT SIGNAL</b>	RGB Analog
<b>INPUT TERMINALS</b>	Standard VGA D-Sub 15-pin Connector
<b>SYNC SIGNALING</b>	Separate H/V
<b>MEMORY MODES</b>	14 Factory Preset, 14 User-Settable
<b>VESA PLUG AND PLAY LEVEL</b>	DDC2B, DDC1
<b>DIGITAL ON-SCREEN CONTROLS</b>	Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase (+/-), 5 Language Select, Image Size Auto-Adjust, OSD Position, Color Temp (9300K, 6500K, User), Information, LightView
<b>FRONT PANEL CONTROLS</b>	Power, Menu, Adjust (Up/Down/Left/Right), Auto-Set, LightView
<b>POWER REQUIREMENTS</b>	90-264 VAC, 50-60Hz
<b>DPMS POWER CONSUMPTION</b>	On: 28 Watts, Standby: 3 Watts, DPMS Off: 3 Watts
<b>TILT/SWIVEL</b>	Tilt: Down 5°/Up 30°
<b>VESA MOUNTING COMPLIANCE</b>	Standard VESA Mounting, 75mm x 75mm Screw Spacing
<b>DIMENSIONS WITH BASE (WxDxH)</b>	14.0" x 6.0" x 14.2" (356mm x 152mm x 360mm)
<b>SHIPPING DIMENSIONS (WxDxH)</b>	16.2" x 6.3" x 16.8" (412mm x 160mm x 427mm)
<b>WEIGHT</b>	8.8 lbs (4.0 kg) Net; 12.1 lbs (5.5 kg) Shipping
<b>SAFETY/REGULATORY</b>	TCO'99, UL, FCC-B, EPA Energy Star, CSA, CE, TUV-GS, SEMKO, GOST, ISO 13406-2, C-TICK, VCCI-2
<b>ACCESSORIES</b>	Power Cord, Signal Cable, Manual, Install Disk
<b>LGEUS WARRANTY</b>	3 Year QuickSwap Replacement Program
<b>UPC#</b>	719192165021



LG ELECTRONICS U.S.A., INC.

HEADQUARTERS

1000 Sylvan Avenue, Englewood Cliffs, NJ 07632 ▶ Tel: (201) 816-2000, Fax: (201) 816-2188 ▶ [www.LGusa.com](http://www.LGusa.com)

©2004 LG Electronics U.S.A., Inc. All trademarks are property of their respective owners. Design and specifications subject to change without notice. 4/04

